

## **TYRES**

Product group	Tyres	
Item number	10626386	
Valid tyre size	340 / 85 R 36	
LI / SI / PR	132 D / 129 E	
TL/TT	TL	
Brand	Firestone	
Tread pattern	Performer 85	



## **Notes and features**

- Narrow tyre for maintenance of row crops.
- High load capacity.
- Outstanding driving dynamics on the road.
- Very good traction and self-cleaning.
- Long service life.



## **Technical Informations**

Item number	10626386
EAN	3286340563819
Valid tyre size	340 / 85 R 36
Alternative size 1	13.6R36
LI / SI / PR	132 D / 129 E
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 85
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	77,30
Recommended rim size	12
Permitted rim size	11
Maximum air pressure [bar].	1,60
Section width (mm)	348
Outer diameter of tyre [mm].	1492
Stat. radius (SLR) [mm]	672
Rolling circumference [mm].	4476
Tread depth (mm)	43,0
Number of lugs	22x2
Tyre capacity 75% [ltr.]	186
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
132 D	2000	65		1,60	
129 E	1850	70		1,60	