

TYRES

Product group	Tyres	
Item number	10626438	
Valid tyre size	460 / 85 R 38	
LI / SI / PR	154 D / 151 E	
TL/TT	TL	
Brand	Firestone	
Tread pattern	Performer 85 XL	



Notes and features

- Standard tyre of the 85 series for tractors of the medium power class.
- Tyre with increased load capacity (XL = Extra Load) compared with Performer 85.
- Outstanding driving dynamics and road comfort owing to increased deflection.
- Very good traction with low soil compaction due to patented dual-angle lugs.
- Very good self-cleaning properties.
- Long service life and even wear.



Technical Informations

Item number	10626438
EAN	3286340589314
Valid tyre size	460 / 85 R 38
LI / SI / PR	154 D / 151 E
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 85 XL
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	162,50
Recommended rim size	16
Permitted rim size	15
Maximum air pressure [bar].	2,40
Section width (mm)	496
Outer diameter of tyre [mm].	1761
Stat. radius (SLR) [mm]	793
Rolling circumference [mm].	5323
Tread depth (mm)	50,0
Number of lugs	21x2
Tyre capacity 75% [ltr.]	432
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 D	3750	65		2,40	
151 E	3450	70		2,40	