

TYRES

Product group	Tyres
Item number	10626448
Valid tyre size	520 / 85 R 38
LI / SI / PR	160 D / 157 E
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 85 XL



Bohnenkamp
■ ■ ● Moving Professionals

Notes and features

- Standard tyre of the 85 series for tractors of the medium power class.
- Tyre with increased load capacity (XL = Extra Load) compared with Performer 85.
- Outstanding driving dynamics and road comfort owing to increased deflection.
- Very good traction with low soil compaction due to patented dual-angle lugs.
- Very good self-cleaning properties.
- Long service life and even wear.

Technical Informations

Item number	10626448
EAN	3286340589413
Valid tyre size	520 / 85 R 38
LI / SI / PR	160 D / 157 E
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 85 XL
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	198,16
Recommended rim size	18
Permitted rim size	16
Maximum air pressure [bar].	2,40
Section width (mm)	562
Outer diameter of tyre [mm].	1851
Stat. radius (SLR) [mm]	833
Rolling circumference [mm].	5591
Tread depth (mm)	56,0
Number of lugs	21x2
Tyre capacity 75% [ltr.]	540
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 D	4500	65		2,40	
157 E	4125	70		2,40	