

## **TYRES**

Product group	Tyres
Item number	10626452
Valid tyre size	IF 650 / 85 R 38
LI / SI / PR	179 D / 176 E
TL/TT	TL
Brand	Firestone
Tread pattern	Maxi Traction



## **Notes and features**

- Agricultural tyre for high-performance tractors.
- Very good traction in fields.

- Excellent ride comfort on the road.
- Very low soil compaction.



## **Technical Informations**

Item number	10626452
EAN	3286340546416
Valid tyre size	IF 650 / 85 R 38
LI / SI / PR	179 D / 176 E
TL/TT	TL
Brand	Firestone
Tread pattern	Maxi Traction
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	333,40
Recommended rim size	23
Maximum air pressure [bar].	2,40
Section width (mm)	703
Outer diameter of tyre [mm].	2067
Stat. radius (SLR) [mm]	918
Rolling circumference [mm].	6105
Tread depth (mm)	63,0
Number of lugs	21x2
Tyre capacity 75% [ltr.]	879
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
179 D	7750	65		2,40	
176 E	7100	70		2,40	