

TYRES

Product group	Tyres
Item number	10626475
Valid tyre size	520 / 85 R 42
LI / SI / PR	157 D / 154 E
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 85



Bohnenkamp
■ ■ ● Moving Professionals

Notes and features

- Narrow tyre for maintenance of row crops.
- High load capacity.
- Outstanding driving dynamics on the road.
- Very good traction and self-cleaning.
- Long service life.

Technical Informations

Item number	10626475
EAN	3286340471510
Valid tyre size	520 / 85 R 42
LI / SI / PR	157 D / 154 E
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 85
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	240,40
Recommended rim size	18
Permitted rim size	16
Maximum air pressure [bar].	1,60
Section width (mm)	561
Outer diameter of tyre [mm].	1946
Stat. radius (SLR) [mm]	876
Rolling circumference [mm].	5838
Tread depth (mm)	55,0
Number of lugs	22x2
Tyre capacity 75% [ltr.]	570
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
157 D	4125	65		1,60	
154 E	3750	70		1,60	