

## TYRES

Product group	Tyres
Item number	10626476
Valid tyre size	520 / 85 R 42
LI / SI / PR	162 D / 159 E
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 85 XL



Bohnenkamp  
■ ■ ● Moving Professionals

## Notes and features

- Standard tyre of the 85 series for tractors of the medium power class.
- Tyre with increased load capacity (XL = Extra Load) compared with Performer 85.
- Outstanding driving dynamics and road comfort owing to increased deflection.
- Very good traction with low soil compaction due to patented dual-angle lugs.
- Very good self-cleaning properties.
- Long service life and even wear.

## Technical Informations

Item number	10626476
EAN	3286340471718
Valid tyre size	520 / 85 R 42
Alternative size 1	20.8R42
LI / SI / PR	162 D / 159 E
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 85 XL
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	209,25
Recommended rim size	18
Permitted rim size	16
Maximum air pressure [bar].	2,40
Section width (mm)	561
Outer diameter of tyre [mm].	1946
Stat. radius (SLR) [mm]	875
Rolling circumference [mm].	5892
Tread depth (mm)	55,0
Number of lugs	22x2
Tyre capacity 75% [ltr.]	570
Guarantee period	10 years
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
162 D	4750	65		2,40	
159 E	4375	70		2,40	