

TYRES

| | |
|-----------------|---------------|
| Product group | Tyres |
| Item number | 10626635 |
| Valid tyre size | 420 / 70 R 24 |
| LI / SI / PR | 130 D / 127 E |
| TL/TT | TL |
| Brand | Firestone |
| Tread pattern | Performer 70 |



Bohnenkamp
■ ■ ● Moving Professionals

Notes and features

- Unique double-angle lug technology.
- Large ground contact area due to stronger deflection and flatter tread pattern contour.
- Increased ride comfort.

Technical Informations

| | |
|------------------------------|---------------|
| Item number | 10626635 |
| EAN | 3286340341318 |
| Valid tyre size | 420 / 70 R 24 |
| LI / SI / PR | 130 D / 127 E |
| TL/TT | TL |
| Brand | Firestone |
| Tread pattern | Performer 70 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 74,70 |
| Recommended rim size | 13 |
| Permitted rim size | 12, 14 |
| Maximum air pressure [bar]. | 1,60 |
| Section width (mm) | 421 |
| Outer diameter of tyre [mm]. | 1246 |
| Stat. radius (SLR) [mm] | 560 |
| Rolling circumference [mm]. | 3738 |
| Tread depth (mm) | 41,0 |
| Number of lugs | 18x2 |
| Tyre capacity 75% [ltr.] | 198 |
| Guarantee period | 10 years |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 130 D | 1900 | 65 | | 1,60 | |
| 127 E | 1750 | 70 | | 1,60 | |