

TYRES

Product group	Tyres	
Item number	10626705	
Valid tyre size	480 / 70 R 30	
LI / SI / PR	141 D / 138 E	
TL/TT	TL	
Brand	Firestone	
Tread pattern	Performer 70	



Notes and features

- Unique double-angle lug technology.
- Large ground contact area due to stronger deflection and flatter tread pattern contour.
- Increased ride comfort.



Technical Informations

Item number	10626705
EAN	3286340342018
Valid tyre size	480 / 70 R 30
LI / SI / PR	141 D / 138 E
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 70
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	114,30
Recommended rim size	15
Permitted rim size	14, 16
Maximum air pressure [bar].	1,60
Section width (mm)	486
Outer diameter of tyre [mm].	1489
Stat. radius (SLR) [mm]	670
Rolling circumference [mm].	4467
Tread depth (mm)	47,5
Number of lugs	20x2
Tyre capacity 75% [ltr.]	315
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
141 D	2575	65		1,60	
138 E	2360	70		1,60	