

TYRES

| | |
|-----------------|---------------|
| Product group | Tyres |
| Item number | 10626725 |
| Valid tyre size | 600 / 70 R 30 |
| LI / SI / PR | 158 D / 155 E |
| TL/TT | TL |
| Brand | Firestone |
| Tread pattern | Maxi Traction |



Notes and features

- Agricultural tyre for high-performance tractors.
- Very good traction in fields.
- Excellent ride comfort on the road.
- Very low soil compaction.

Technical Informations

| | |
|------------------------------|---------------|
| Item number | 10626725 |
| EAN | 3286340543811 |
| Valid tyre size | 600 / 70 R 30 |
| LI / SI / PR | 158 D / 155 E |
| TL/TT | TL |
| Brand | Firestone |
| Tread pattern | Maxi Traction |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 206,38 |
| Recommended rim size | 20 |
| Permitted rim size | 18 |
| Maximum air pressure [bar]. | 2,40 |
| Section width (mm) | 618 |
| Outer diameter of tyre [mm]. | 1622 |
| Stat. radius (SLR) [mm] | 722 |
| Rolling circumference [mm]. | 4867 |
| Tread depth (mm) | 57,0 |
| Number of lugs | 19x2 |
| Tyre capacity 75% [litr.] | 450 |
| Guarantee period | 10 years |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 158 D | 4250 | 65 | | 2,40 | |
| 155 E | 3875 | 70 | | 2,40 | |