

TYRES

Product group	Tyres
Item number	10626726
Valid tyre size	IF 600 / 70 R 30
LI / SI / PR	165 D / 161 E
TL/TT	TL
Brand	Firestone
Tread pattern	Maxi Traction



Notes and features

- Agricultural tyre for high-performance tractors.
- Very good traction in fields.
- Excellent ride comfort on the road.
- Very low soil compaction.

Technical Informations

Item number	10626726
EAN	3286340546010
Valid tyre size	IF 600 / 70 R 30
LI / SI / PR	165 D / 161 E
TL/TT	TL
Brand	Firestone
Tread pattern	Maxi Traction
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	201,08
Recommended rim size	20
Permitted rim size	21
Maximum air pressure [bar].	2,40
Section width (mm)	618
Outer diameter of tyre [mm].	1622
Stat. radius (SLR) [mm]	709
Rolling circumference [mm].	4855
Tread depth (mm)	57,0
Number of lugs	19x2
Tyre capacity 75% [ltr.]	450
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
165 D	5150	65		2,40	
161 E	4625	70		2,40	