# Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	10626782	
Valid tyre size	IF 710 / 70 R 38	
LI / SI / PR	178 D / 175 E	
TL/TT	TL	
Brand	Firestone	
Tread pattern	Maxi Traction	



#### Notes and features

- Agricultural tyre for high-performance tractors.
- Very good traction in fields.

- Excellent ride comfort on the road.
- Very low soil compaction.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

## Bohnenkamp Moving Professionals

### **Technical Informations**

Item number	10626782
EAN	3286340408813
Valid tyre size	IF 710 / 70 R 38
LI / SI / PR	178 D / 175 E
TL/TT	TL
Brand	Firestone
Tread pattern	Maxi Traction
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	308,59
Recommended rim size	23
Permitted rim size	25
Maximum air pressure [bar].	2,40
Section width (mm)	731
Outer diameter of tyre [mm].	1970
Stat. radius (SLR) [mm]	872
Rolling circumference [mm].	5903
Tread depth (mm)	58,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	800.25
Guarantee period	10 years
E-Ready	No

22.09.2024

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
178 D	7500	65		2,40	
175 E	6900	70		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.