# Bohnenkamp Moving Professionals

TYRES

Product group	Tyres	
Item number	10626795	
Valid tyre size	580 / 70 R 42	
LI / SI / PR	158 D / 155 E	
TL/TT	TL	
Brand	Firestone	
Tread pattern	Performer 70 XL	



#### Notes and features

- Unique double-angle lug technology.
- Large ground contact area due to stronger deflection and flatter tread pattern contour.
- Increased ride comfort.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

## Bohnenkamp Moving Professionals

### **Technical Informations**

Item number	10626795
EAN	3286340564410
Valid tyre size	580 / 70 R 42
LI / SI / PR	158 D / 155 E
TL/TT	ть
Brand	Firestone
Tread pattern	Performer 70 XL
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	227,50
Recommended rim size	18
Maximum air pressure [bar].	1,60
Section width (mm)	573
Outer diameter of tyre [mm].	1894
Stat. radius (SLR) [mm]	853
Rolling circumference [mm].	5682
Tread depth (mm)	54,0
Number of lugs	21x2
Tyre capacity 75% [ltr.]	517.5
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 D	4250	65		1,60	
155 E	3875	70		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.