

TYRES

Product group	Tyres
Item number	10626802
Valid tyre size	IF 620 / 70 R 42
LI / SI / PR	172 D / 169 E
TL/TT	TL
Brand	Firestone
Tread pattern	Maxi Traction



Notes and features

- Agricultural tyre for high-performance tractors.
- Very good traction in fields.
- Excellent ride comfort on the road.
- Very low soil compaction.

Technical Informations

Item number	10626802
EAN	3286340546119
Valid tyre size	IF 620 / 70 R 42
LI / SI / PR	172 D / 169 E
TL/TT	TL
Brand	Firestone
Tread pattern	Maxi Traction
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	263,40
Recommended rim size	20
Permitted rim size	21
Maximum air pressure [bar].	2,40
Section width (mm)	632
Outer diameter of tyre [mm].	1966
Stat. radius (SLR) [mm]	869
Rolling circumference [mm].	5891
Tread depth (mm)	57,0
Number of lugs	22x2
Tyre capacity 75% [ltr.]	612.75
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
172 D	6300	65		2,40	
169 E	5800	70		2,40	