

## **TYRES**

Product group	Tyres	
Item number	10627132	
Valid tyre size	440 / 65 R 28	
LI / SI / PR	131 D / 128 E	
TL/TT	TL	
Brand	Firestone	
Tread pattern	Maxi Traction 65	



## **Notes and features**

- Agricultural tyre for high-performance tractors.
- Very good traction in fields.

- Excellent ride comfort on the road.
- Very low soil compaction.



## **Technical Informations**

Item number	10627132
EAN	3286340894517
Valid tyre size	440 / 65 R 28
LI / SI / PR	131 D / 128 E
TL/TT	TL
Brand	Firestone
Tread pattern	Maxi Traction 65
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	81,91
Recommended rim size	14
Permitted rim size	13, 15
Maximum air pressure [bar].	1,60
Section width (mm)	436
Outer diameter of tyre [mm].	1277
Stat. radius (SLR) [mm]	583
Rolling circumference [mm].	3834
Tread depth (mm)	42,5
Number of lugs	20x2
Tyre capacity 75% [ltr.]	193.5
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
131 D	1950	65		1,60	
128 E	1800	70		1,60	