

## **TYRES**

Product group	Tyres	
Item number	10627165	
Valid tyre size	600 / 65 R 28	
LI / SI / PR	154 D / 151 E	
TL/TT	TL	
Brand	Firestone	
Tread pattern	Maxi Traction	



## **Notes and features**

- Agricultural tyre for high-performance tractors.
- Very good traction in fields.

- Excellent ride comfort on the road.
- Very low soil compaction.



## **Technical Informations**

Item number	10627165
EAN	3286340544610
Valid tyre size	600 / 65 R 28
LI / SI / PR	154 D / 151 E
TL/TT	TL
Brand	Firestone
Tread pattern	Maxi Traction
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	166,68
Recommended rim size	20
Permitted rim size	18
Maximum air pressure [bar].	2,40
Section width (mm)	617
Outer diameter of tyre [mm].	1498
Stat. radius (SLR) [mm]	670
Rolling circumference [mm].	4518
Tread depth (mm)	51,0
Number of lugs	18x2
Tyre capacity 75% [ltr.]	405
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 D	3750	65		2,40	
151 E	3450	70		2,40	