

TYRES

Product group	Tyres
Item number	10627175
Valid tyre size	540 / 65 R 30
LI / SI / PR	143 D / 140 E
TL/TT	TL
Brand	Firestone
Tread pattern	Maxi Traction 65



Bohnenkamp
■ ■ ■ Moving Professionals

Notes and features

- Agricultural tyre for high-performance tractors.
- Very good traction in fields.
- Excellent ride comfort on the road.
- Very low soil compaction.

Technical Informations

Item number	10627175
EAN	3286340896313
Valid tyre size	540 / 65 R 30
LI / SI / PR	143 D / 140 E
TL/TT	TL
Brand	Firestone
Tread pattern	Maxi Traction 65
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	134,86
Recommended rim size	16
Permitted rim size	18
Maximum air pressure [bar].	1,60
Section width (mm)	521
Outer diameter of tyre [mm].	1462
Stat. radius (SLR) [mm]	659
Rolling circumference [mm].	4386
Tread depth (mm)	45,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	333
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
143 D	2725	65		1,60	
140 E	2500	70		1,60	