

TYRES

Product group	Tyres
Item number	10627181
Valid tyre size	800 / 65 R 32
LI / SI / PR	178 A8 / 178 B
TL/TT	TL
Brand	Firestone
Tread pattern	Maxi Traction



Notes and features

- Agricultural tyre for high-performance tractors.
- Very good traction in fields.

- Excellent ride comfort on the road.
- Very low soil compaction.



Technical Informations

Item number	10627181
EAN	3286340590518
Valid tyre size	800 / 65 R 32
LI / SI / PR	178 A8 / 178 B
TL/TT	TL
Brand	Firestone
Tread pattern	Maxi Traction
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	272,00
Recommended rim size	27
Permitted rim size	25
Maximum air pressure [bar].	3,20
Section width (mm)	824
Outer diameter of tyre [mm].	1854
Stat. radius (SLR) [mm]	834
Rolling circumference [mm].	5548
Tread depth (mm)	58,0
Number of lugs	17x2
Tyre capacity 75% [ltr.]	853.5
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
178 A8	7500	40		3,20	
178 B	7500	50		3,20	