

## TYRES

Product group	Tyres
Item number	10627252
Valid tyre size	650 / 65 R 42
LI / SI / PR	158 D / 155 E
TL/TT	TL
Brand	Firestone
Tread pattern	Maxi Traction 65



Bohnenkamp  
■ ■ ■ Moving Professionals

## Notes and features

- Agricultural tyre for high-performance tractors.
- Very good traction in fields.
- Excellent ride comfort on the road.
- Very low soil compaction.

## Technical Informations

Item number	10627252
EAN	3286340898911
Valid tyre size	650 / 65 R 42
LI / SI / PR	158 D / 155 E
TL/TT	TL
Brand	Firestone
Tread pattern	Maxi Traction 65
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	243,87
Recommended rim size	20
Maximum air pressure [bar].	1,60
Section width (mm)	625
Outer diameter of tyre [mm].	1926
Stat. radius (SLR) [mm]	861
Rolling circumference [mm].	5809
Tread depth (mm)	54,0
Number of lugs	21x2
Tyre capacity 75% [ltr.]	647.25
Guarantee period	10 years
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 D	4250	65		1,60	
155 E	3875	70		1,60	