

TYRES

Product group	Tyres
Item number	10627304
Valid tyre size	270 / 95 R 32
LI / SI / PR	150 A2 / 136 D
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 95



Notes and features

- Narrow tyre for maintenance of row crops.
- High load capacity.
- Outstanding driving dynamics on the road.
- Very good traction and self-cleaning.
- Long service life.



Technical Informations

Item number	10627304
EAN	3286340603218
Valid tyre size	270 / 95 R 32
LI / SI / PR	150 A2 / 136 D
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 95
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	80,00
Recommended rim size	9
Permitted rim size	8, 10
Maximum air pressure [bar].	4,00
Section width (mm)	267
Outer diameter of tyre [mm].	1329
Stat. radius (SLR) [mm]	629
Rolling circumference [mm].	4092
Tread depth (mm)	33,0
Number of lugs	29x2
Tyre capacity 75% [ltr.]	104.25
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
150 A2	3350	10		4,00	
136 D	2240	65		4,00	