

TYRES

Product group	Tyres
Item number	10627332
Valid tyre size	300 / 95 R 46
LI / SI / PR	162 A2 / 148 D
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 95



Bohnenkamp
■ ■ ● Moving Professionals

Notes and features

- Narrow tyre for maintenance of row crops.
- High load capacity.
- Outstanding driving dynamics on the road.
- Very good traction and self-cleaning.
- Long service life.

Technical Informations

Item number	10627332
EAN	3286340604017
Valid tyre size	300 / 95 R 46
LI / SI / PR	162 A2 / 148 D
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 95
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	115,00
Recommended rim size	10
Permitted rim size	9, 11
Maximum air pressure [bar].	4,00
Section width (mm)	313
Outer diameter of tyre [mm].	1737
Stat. radius (SLR) [mm]	822
Rolling circumference [mm].	5348
Tread depth (mm)	33,0
Number of lugs	34x2
Tyre capacity 75% [ltr.]	179.25
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
162 A2	4750	10		4,00	
148 D	3150	65		4,00	