

TYRES

Product group	Tyres
Item number	10627381
Valid tyre size	460 / 70 R 24
LI / SI / PR	159 A8 / 159 B
TL/TT	TL
Brand	Firestone
Tread pattern	R8000 Utility



Notes and features

- Suitable for industrial use and simple, multi-purpose applications in agriculture.
- Excellent lateral stability and safety.
- Cut and puncture resistant.
- Solid grip on hard surfaces.

Technical Informations

Item number	10627381
EAN	3286341047417
Valid tyre size	460 / 70 R 24
LI / SI / PR	159 A8 / 159 B
TL/TT	TL
Brand	Firestone
Tread pattern	R8000 Utility
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	93,70
Recommended rim size	W15L
Permitted rim size	W14L, DW14L, DW15L
Maximum air pressure [bar].	4,00
Section width (mm)	486
Outer diameter of tyre [mm].	1274
Stat. radius (SLR) [mm]	573
Rolling circumference [mm].	3850
Tread depth (mm)	31,0
Number of lugs	27x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
159 A8	4375	40		4,00	
159 B	4375	50		4,00	