

TYRES

Product group	Tyres	
Item number	10628150	
Valid tyre size	500 / 70 R 24	
LI / SI / PR	164 A8 / 164 B	
TL/TT	TL	
Brand	Firestone	
Tread pattern	Duraforce Utility	



Notes and features

- For light industrial use.
- Very good traction on hard surfaces.
- Excellent stability.

- Even wear.
- Cut and shock resistant.



Technical Informations

Item number	10628150
EAN	3286340602914
Valid tyre size	500 / 70 R 24
LI / SI / PR	164 A8 / 164 B
TL/TT	TL
Brand	Firestone
Tread pattern	Duraforce Utility
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	133,50
Recommended rim size	DW16L
Permitted rim size	DW15L
Maximum air pressure [bar].	4,00
Section width (mm)	520
Outer diameter of tyre [mm].	1329
Stat. radius (SLR) [mm]	598
Rolling circumference [mm].	4012
Tyre capacity 75% [ltr.]	261
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 A8	5000	40		4,00	
164 B	5000	50		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.