

TYRES

Product group	Tyres	
Item number	10629030	
Valid tyre size	VF 540 / 65 R 28 NRO	
LI / SI / PR	154 D / 151 E	
TL/TT	TL	
Brand	Bridgestone	
Tread pattern	VT Tractor	





Notes and features

- High load capacity thanks to VF-Ultraflex technology.
- Low tyre pressure, even with heavy loads.
- Very good traction und high ride comfort.
- Thanks to NRO technology (Narrow Rim Option), the tyre can be mounted on a narrower rim than other VF or IF tyres of the same dimension.



Technical Informations

Item number	10629030
EAN	3286340694919
Valid tyre size	VF 540 / 65 R 28 NRO
LI / SI / PR	154 D / 151 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VT Tractor
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	127,50
Recommended rim size	18
Permitted rim size	16
Maximum air pressure [bar].	1,60
Section width (mm)	528
Outer diameter of tyre [mm].	1404
Stat. radius (SLR) [mm]	606
Rolling circumference [mm].	4164
Tread depth (mm)	44,0
Number of lugs	18x2
Tyre capacity 75% [ltr.]	307.5
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
154 D	3750	65		1,60	
151 E	3450	70		1,60	