

TYRES

Product group	Tyres
Item number	10629058
Valid tyre size	VF 540 / 65 R 30 NRO
LI / SI / PR	155 D / 152 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VT Tractor



Bohnenkamp
■ ■ ● Moving Professionals

BRIDGESTONE

Notes and features

- High load capacity thanks to VF-Ultraflex technology.
- Low tyre pressure, even with heavy loads.
- Very good traction und high ride comfort.
- Thanks to NRO technology (Narrow Rim Option), the tyre can be mounted on a narrower rim than other VF or IF tyres of the same dimension.

Technical Informations

Item number	10629058
EAN	3286340695213
Valid tyre size	VF 540 / 65 R 30 NRO
LI / SI / PR	155 D / 152 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VT Tractor
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	116,90
Recommended rim size	18
Permitted rim size	16
Maximum air pressure [bar].	1,60
Section width (mm)	528
Outer diameter of tyre [mm].	1464
Stat. radius (SLR) [mm]	630
Rolling circumference [mm].	4337
Tread depth (mm)	44,0
Number of lugs	19x2
Tyre capacity 75% [litr.]	315
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
155 D	3875	65		1,60	
152 E	3550	70		1,60	