

TYRES

Product group	Tyres
Item number	10629066
Valid tyre size	VF 600 / 65 R 34
LI / SI / PR	163 D / 159 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VT Tractor



BRIDGESTONE

Notes and features

- High load capacity thanks to VF-Ultraflex technology.
- Low tyre pressure, even with heavy loads.
- Very good traction und high ride comfort.
- Thanks to NRO technology (Narrow Rim Option), the tyre can be mounted on a narrower rim than other VF or IF tyres of the same dimension.

Technical Informations

Item number	10629066
EAN	3286340695619
Valid tyre size	VF 600 / 65 R 34
LI / SI / PR	163 D / 159 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VT Tractor
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	171,40
Recommended rim size	21
Permitted rim size	20
Maximum air pressure [bar].	1,60
Section width (mm)	597
Outer diameter of tyre [mm].	1644
Stat. radius (SLR) [mm]	706
Rolling circumference [mm].	4866
Tread depth (mm)	51,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	452.25
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
163 D	4875	65		1,60	
159 E	4375	70		1,60	