

## TYRES

Product group	Tyres
Item number	10629070
Valid tyre size	VF 600 / 70 R 34
LI / SI / PR	167 D / 164 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VT Tractor



**BRIDGESTONE**

## Notes and features

- High load capacity thanks to VF-Ultraflex technology.
- Low tyre pressure, even with heavy loads.
- Very good traction und high ride comfort.
- Thanks to NRO technology (Narrow Rim Option), the tyre can be mounted on a narrower rim than other VF or IF tyres of the same dimension.

## Technical Informations

Item number	10629070
EAN	3286340695718
Valid tyre size	VF 600 / 70 R 34
LI / SI / PR	167 D / 164 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VT Tractor
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	309,00
Recommended rim size	21
Permitted rim size	20
Maximum air pressure [bar].	1,60
Section width (mm)	603
Outer diameter of tyre [mm].	1708
Stat. radius (SLR) [mm]	740
Rolling circumference [mm].	5071
Tread depth (mm)	54,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	509.25
Guarantee period	10 years
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
167 D	5450	65		1,60	
164 E	5000	70		1,60	