

TYRES

Product group	Tyres
Item number	10629072
Valid tyre size	VF 710 / 60 R 34 NRO
LI / SI / PR	169 D / 166 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VT Tractor



BRIDGESTONE

Notes and features

- High load capacity thanks to VF-Ultraflex technology.
- Low tyre pressure, even with heavy loads.
- Very good traction und high ride comfort.
- Thanks to NRO technology (Narrow Rim Option), the tyre can be mounted on a narrower rim than other VF or IF tyres of the same dimension.

Technical Informations

Item number	10629072
EAN	3286340695817
Valid tyre size	VF 710 / 60 R 34 NRO
LI / SI / PR	169 D / 166 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VT Tractor
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	220,00
Recommended rim size	25
Permitted rim size	23
Maximum air pressure [bar].	1,60
Section width (mm)	708
Outer diameter of tyre [mm].	1716
Stat. radius (SLR) [mm]	736
Rolling circumference [mm].	5044
Tread depth (mm)	58,0
Number of lugs	19x2
Tyre capacity 75% [ltr.]	600
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
169 D	5800	65		1,60	
166 E	5300	70		1,60	