

TYRES

| | |
|-----------------|----------------------|
| Product group | Tyres |
| Item number | 10629076 |
| Valid tyre size | VF 650 / 65 R 38 NRO |
| LI / SI / PR | 169 D / 166 E |
| TL/TT | TL |
| Brand | Bridgestone |
| Tread pattern | VT Tractor |



Bohnenkamp
■ ■ ● Moving Professionals

BRIDGESTONE

Notes and features

- High load capacity thanks to VF-Ultraflex technology.
- Low tyre pressure, even with heavy loads.
- Very good traction und high ride comfort.
- Thanks to NRO technology (Narrow Rim Option), the tyre can be mounted on a narrower rim than other VF or IF tyres of the same dimension.

Technical Informations

| | |
|------------------------------|----------------------|
| Item number | 10629076 |
| EAN | 3286340696012 |
| Valid tyre size | VF 650 / 65 R 38 NRO |
| LI / SI / PR | 169 D / 166 E |
| TL/TT | TL |
| Brand | Bridgestone |
| Tread pattern | VT Tractor |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 216,20 |
| Recommended rim size | 23 |
| Permitted rim size | 21, 20 |
| Maximum air pressure [bar]. | 1,60 |
| Section width (mm) | 650 |
| Outer diameter of tyre [mm]. | 1801 |
| Stat. radius (SLR) [mm] | 779 |
| Rolling circumference [mm]. | 5424 |
| Tread depth (mm) | 51,5 |
| Number of lugs | 19x2 |
| Tyre capacity 75% [litr.] | 597 |
| Guarantee period | 10 years |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 169 D | 5800 | 65 | | 1,60 | |
| 166 E | 5300 | 70 | | 1,60 | |