

## TYRES

Product group	Tyres
Item number	10629078
Valid tyre size	VF 650 / 85 R 38
LI / SI / PR	179 D / 176 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VT Tractor



**BRIDGESTONE**

## Notes and features

- High load capacity thanks to VF-Ultraflex technology.
- Low tyre pressure, even with heavy loads.
- Very good traction und high ride comfort.
- Thanks to NRO technology (Narrow Rim Option), the tyre can be mounted on a narrower rim than other VF or IF tyres of the same dimension.

## Technical Informations

Item number	10629078
EAN	3286340696111
Valid tyre size	VF 650 / 85 R 38
LI / SI / PR	179 D / 176 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VT Tractor
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	335,80
Recommended rim size	23
Permitted rim size	21, 20
Maximum air pressure [bar].	1,60
Section width (mm)	663
Outer diameter of tyre [mm].	2071
Stat. radius (SLR) [mm]	875
Rolling circumference [mm].	6027
Tread depth (mm)	61,0
Number of lugs	22x2
Tyre capacity 75% [ltr.]	839.25
Guarantee period	10 years
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
179 D	7750	65		1,60	
176 E	7100	70		1,60	