

## TYRES

Product group	Tyres
Item number	10629090
Valid tyre size	VF 650 / 65 R 42 NRO
LI / SI / PR	170 D / 167 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VT Tractor



**BRIDGESTONE**

## Notes and features

- High load capacity thanks to VF-Ultraflex technology.
- Low tyre pressure, even with heavy loads.
- Very good traction und high ride comfort.
- Thanks to NRO technology (Narrow Rim Option), the tyre can be mounted on a narrower rim than other VF or IF tyres of the same dimension.

## Technical Informations

Item number	10629090
EAN	3286340696517
Valid tyre size	VF 650 / 65 R 42 NRO
LI / SI / PR	170 D / 167 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VT Tractor
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	244,00
Recommended rim size	23
Permitted rim size	21, 20
Maximum air pressure [bar].	1,60
Section width (mm)	650
Outer diameter of tyre [mm].	1922
Stat. radius (SLR) [mm]	820
Rolling circumference [mm].	5818
Tread depth (mm)	51,5
Number of lugs	20x2
Tyre capacity 75% [ltr.]	639
Guarantee period	10 years
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
170 D	6000	65		1,60	
167 E	5450	70		1,60	