

## TYRES

Product group	Tyres
Item number	10629112
Valid tyre size	VF 900 / 50 R 42 NRO
LI / SI / PR	180 D / 177 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VT Tractor



**BRIDGESTONE**

## Notes and features

- High load capacity thanks to VF-Ultraflex technology.
- Low tyre pressure, even with heavy loads.
- Very good traction und high ride comfort.
- Thanks to NRO technology (Narrow Rim Option), the tyre can be mounted on a narrower rim than other VF or IF tyres of the same dimension.

## Technical Informations

Item number	10629112
EAN	3286340696814
Valid tyre size	VF 900 / 50 R 42 NRO
LI / SI / PR	180 D / 177 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VT Tractor
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	335,80
Recommended rim size	30
Permitted rim size	28
Maximum air pressure [bar].	1,60
Section width (mm)	881
Outer diameter of tyre [mm].	1967
Stat. radius (SLR) [mm]	844
Rolling circumference [mm].	5831
Tread depth (mm)	65,0
Number of lugs	18x2
Tyre capacity 75% [ltr.]	921.75
Guarantee period	10 years
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
180 D	8000	65		1,60	
177 E	7300	70		1,60	