

## TYRES

Product group	Tyres
Item number	10629114
Valid tyre size	VF 900 / 60 R 42 NRO
LI / SI / PR	185 D / 182 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VT Tractor



Bohnenkamp  
■ ■ ● Moving Professionals

**BRIDGESTONE**

## Notes and features

- High load capacity thanks to VF-Ultraflex technology.
- Low tyre pressure, even with heavy loads.
- Very good traction und high ride comfort.
- Thanks to NRO technology (Narrow Rim Option), the tyre can be mounted on a narrower rim than other VF or IF tyres of the same dimension.

## Technical Informations

Item number	10629114
EAN	3286340696913
Valid tyre size	VF 900 / 60 R 42 NRO
LI / SI / PR	185 D / 182 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VT Tractor
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	360,00
Recommended rim size	30
Permitted rim size	28
Maximum air pressure [bar].	1,60
Section width (mm)	851
Outer diameter of tyre [mm].	2147
Stat. radius (SLR) [mm]	921
Rolling circumference [mm].	6304
Tread depth (mm)	65,0
Number of lugs	19x2
Tyre capacity 75% [ltr.]	1147.5
Guarantee period	10 years
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
185 D	9250	65		1,60	
182 E	8500	70		1,60	