

TYRES

Product group	Tyres	
Item number	10691800	
Valid tyre size	315 / 80 D 16	
LI / SI / PR	104 A6, 6 PR	
TL/TT	TL	
Brand	Bridgestone	
Tread pattern	M40B	





Notes and features

- The Bridgestone M-40B was designed for mowers.
- It provides good traction and better grip on slopes.
- Its tread pattern protects soil and prevents damage to turf.



Technical Informations

Item number	10691800
EAN	3286340333214
Valid tyre size	315 / 80 D 16
LI / SI / PR	104 A6, 6 PR
TL/TT	TL
Brand	Bridgestone
Tread pattern	M40B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	38,00
Recommended rim size	10LB
Maximum air pressure [bar].	1,60
Section width (mm)	316
Outer diameter of tyre [mm].	910
Stat. radius (SLR) [mm]	415
Rolling circumference [mm].	2659
Tread depth (mm)	9,1
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
104 A6	900	30		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.