

TYRES

Product group	Tyres	
Item number	10714940	
Valid tyre size	20.5 x 8.0 - 10	
LI / SI / PR	98 M, 10 PR	
TL/TT	TL	
Brand	Trailermaxx	
Tread pattern	C834	





Notes and features

- The C-834 Trailermaxx was developed for trailers and caravans.
- Its reinforced construction enables maximum loading capacity.
- Thanks to its optimum height and width ratio, the tyre provides high ride comfort and smooth running.



Technical Informations

Item number	10714940
EAN	6933882587823
Valid tyre size	20.5 x 8.0 - 10
LI / SI / PR	98 M, 10 PR
TL/TT	TL
Brand	Trailermaxx
Tread pattern	C834
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	8,70
Recommended rim size	6.001
Maximum air pressure [bar].	6,25
Section width (mm)	200
Outer diameter of tyre [mm].	520
Stat. radius (SLR) [mm]	245
Rolling circumference [mm].	1612
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
98 M	750	130		6,25	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.