

TYRES

Product group	Tyres
Item number	10744021
Valid tyre size	4.80 / 4.00 - 8
LI / SI / PR	70 M, 6 PR
TL/TT	тт
SET	Tube
Brand	Trailermaxx
Tread pattern	C178





Notes and features

- The C-178 Trailermaxx was developed for trailers and caravans.
- It is characterised above all by a high speed index with maximum load capacity.
- Thanks to its optimum height and width ratio, the tyre provides high ride comfort and smooth running.



Technical Informations

Item number	10744021
EAN	4717784800011
Valid tyre size	4.80 / 4.00 - 8
LI / SI / PR	70 M, 6 PR
TL/TT	тт
SET	Tube
Valve designation	TR 13
Brand	Trailermaxx
Tread pattern	C178
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	3,30
Recommended rim size	3.75
Maximum air pressure [bar].	6,30
Section width (mm)	128
Outer diameter of tyre [mm].	418
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
70 M	335	130		6,30	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.