

TYRES

Product group	Tyres	
Item number	10745197	
Valid tyre size	195 / 50 R 13 C	
LI / SI / PR	104 / 101 N	
TL/TT	TL	
Brand	Cheng Shin	
Tread pattern	Trailermaxx ECO CL-31N	



Notes and features

- The Trailermaxx ECO CL-31N is a tyre for car trailers and caravans.
- The low rolling resistance and optimised tyre weight ensure low fuel consumption.
- Thanks to its high tread pattern depth, the tyre is very durable.



Technical Informations

Item number	10745197
EAN	6933882547995
Valid tyre size	195 / 50 R 13 C
LI / SI / PR	104 / 101 N
TL/TT	TL
Brand	Cheng Shin
Tread pattern	Trailermaxx ECO CL-31N
Rolling resistance	С
Wet grip	В
Rolling noise [db].	72
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	7,96
Recommended rim size	63
Permitted rim size	5.50J, 6.50J, 7J
Maximum air pressure [bar].	6,25
Section width (mm)	188
Outer diameter of tyre [mm].	525
Rolling circumference [mm].	1591
Tread depth (mm)	8,0
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
104 N	900	140	Single	6,25	
101 N	825	140	Twin	6,25	