

TYRES

Product group	Tyres
Item number	10866510
Valid tyre size	295 / 80 R 22.5
LI / SI / PR	152 / 148 M, 16 PR
TL/TT	TL
Brand	Deestone
Tread pattern	SS433



Bohnenkamp
■ ■ ● Moving Professionals

DEESTONE

Notes and features

- The Deestone SS433 is a truck drive wheel tyre for use in regional transport.
- Its block tread pattern with widened blocks at the tyre shoulder provides particularly good grip and traction.
- The tyre offers excellent all-season performance on dry, wet and snowy roads.
- Its rubber compound and casing construction provide high loading capacities and long tyre durability.

Technical Informations

Item number	10866510
EAN	4040658085505
Valid tyre size	295 / 80 R 22.5
LI / SI / PR	152 / 148 M, 16 PR
TL/TT	TL
Brand	Deestone
Tread pattern	SS433
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Rolling resistance	D
Wet grip	B
Rolling noise [db].	76
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	72,80
Recommended rim size	9.00
Maximum air pressure [bar].	8,50
Section width (mm)	306
Outer diameter of tyre [mm].	1063
Stat. radius (SLR) [mm]	495
Rolling circumference [mm].	3110
Tread depth (mm)	20,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 M	3550	130	Single	8,50	
148 M	3150	130	Twin	8,50	