

TYRES

Product group	Tyres
Item number	10866615
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	158 / 156 L, 20 PR
TL/TT	TL
Brand	Deestone
Tread pattern	SK421



Bohnenkamp
■ ■ ● Moving Professionals

DEESTONE

Notes and features

- The Deestone SK421 is a truck tyre for all axles for mixed use.
- Its tread pattern design with a combination of ribs and blocks provides very high traction and slow wearing.
- Zigzag-shaped grooves provide good grip on wet, dry and snowy road roads.
- Thanks to its abrasion-resistant rubber compound, the tyre is excellently suited to on- and off-road use and protected from cut and tear damages.

Technical Informations

Item number	10866615
EAN	4040658088087
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	158 / 156 L, 20 PR
TL/TT	TL
Brand	Deestone
Tread pattern	SK421
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/RA/TR
Rolling resistance	E
Wet grip	C
Rolling noise [db].	71
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	67,20
Recommended rim size	9.00
Maximum air pressure [bar].	9,00
Section width (mm)	312
Outer diameter of tyre [mm].	1076
Stat. radius (SLR) [mm]	844
Rolling circumference [mm].	3217
Tread depth (mm)	17,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 L	4250	120	Single	9,00	
156 L	4000	120	Twin	9,00	