Bohnenkamp Moving Professionals

20.09.2024

TYRES

Product group	Tyres
Item number	10913020
Valid tyre size	28 x 9.00 - 15
LI / SI / PR	102 A5, 6 PR
TL/TT	ТТ
Brand	Mitas
Tread pattern	AC 30



Mitas

Notes and features

• Robust construction machine tread pattern.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10913020
EAN	8059971069594
Valid tyre size	28 x 9.00 - 15
LI / SI / PR	102 A5, 6 PR
TL/TT	TT
Brand	Mitas
Tread pattern	AC 30
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	13,88
Recommended rim size	7.001
Permitted rim size	6.50K
Maximum air pressure [bar].	2,50
Section width (mm)	234
Outer diameter of tyre [mm].	710
Stat. radius (SLR) [mm]	322
Rolling circumference [mm].	2160
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
102 A5	850	25		2,50	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.