

TYRES

Product group	Tyres	
Item number	10915100	
Valid tyre size	440 / 50 R 17	
LI / SI / PR	135 D	
TL/TT	TL	
Brand	Mitas	
Tread pattern	AR-04	



Mitas

Notes and features

- The AR-04 is a radial traction tyre with excellent transport performance for grassland use.
- Thanks to its optimised tread pattern design, the tyre provides good turf protection and is the perfect choice in sloping terrains.
- Smooth running up to 65 km/h.



Technical Informations

Item number	10915100
EAN	8059971034950
Valid tyre size	440 / 50 R 17
LI / SI / PR	135 D
TL/TT	TL
Brand	Mitas
Tread pattern	AR-04
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	55,50
Recommended rim size	14.00
Permitted rim size	13.00
Maximum air pressure [bar].	3,60
Section width (mm)	441
Outer diameter of tyre [mm].	873
Stat. radius (SLR) [mm]	393
Rolling circumference [mm].	2605
Tread depth (mm)	22,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
135 D	2180	65		3,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.