

TYRES

Product group	Tyres	
Item number	10915150	
Valid tyre size	355 / 60 R 18	
LI / SI / PR	142 J	
TL/TT	TL	
Brand	Mitas	
Tread pattern	AR-05	



Mitas

Notes and features

- The AR-05 is a radial tyre for use on agricultural and municipal trailers up to 100 km/h.
- Its all-steel construction effectively protects the tyre against damages.
- The unique tread pattern design and the rounded shoulders provide low rolling resistance.



Technical Informations

Item number	10915150
EAN	8059971043938
Valid tyre size	355 / 60 R 18
Alternative size 1	325/65R18
LI / SI / PR	142 J
TL/TT	TL
Brand	Mitas
Tread pattern	AR-05
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	42,00
Recommended rim size	11
Maximum air pressure [bar].	5,00
Section width (mm)	352
Outer diameter of tyre [mm].	890
Stat. radius (SLR) [mm]	398
Rolling circumference [mm].	2650
Tread depth (mm)	7,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
142 J	2650	100		5,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.