

TYRES

Product group	Tyres	
Item number	10915620	
Valid tyre size	710 / 50 R 26.5	
LI / SI / PR	170 D	
TL/TT	TL	
Brand	Mitas	
Tread pattern	Agriterra 02	



Mitas

Notes and features

- The Mitas Agriterra 02 is a flotation radial tyre for agricultural trailers.
- Thanks to the strong steel belt casing and the special tread pattern, the tyre is not susceptible to damages.
- Due to its large contact area, the soil is optimally protected.



Technical Informations

Item number	10915620
EAN	8059971038347
Valid tyre size	710 / 50 R 26.5
LI / SI / PR	170 D
TL/TT	TL
Brand	Mitas
Tread pattern	Agriterra 02
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	189,70
Recommended rim size	AG24.00
Permitted rim size	AG20.00
Maximum air pressure [bar].	4,00
Section width (mm)	737
Outer diameter of tyre [mm].	1388
Stat. radius (SLR) [mm]	628
Rolling circumference [mm].	4189
Tread depth (mm)	26,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
170 D	6000	65		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.