

## **TYRES**

Product group	Tyres
Item number	10926210
Valid tyre size	750 / 65 R 26
LI / SI / PR	169 A8 / 166 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT



Mitas

## Notes and features

- The Mitas SFT was developed for high-performance machines above180 hp.
- Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.



## **Technical Informations**

Item number	10926210
EAN	8059971067149
Valid tyre size	750 / 65 R 26
LI / SI / PR	169 A8 / 166 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	238,70
Recommended rim size	25
Permitted rim size	23
Maximum air pressure [bar].	2,40
Section width (mm)	738
Outer diameter of tyre [mm].	1620
Stat. radius (SLR) [mm]	720
Speed Radius Index (SRI)	775
Rolling circumference [mm].	4800
Tread depth (mm)	56,0
Number of lugs	20x2
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
169 A8	5800	40		2,40	
166 D	5300	65		2,40	