

TYRES

| | |
|-----------------|----------------|
| Product group | Tyres |
| Item number | 10926481 |
| Valid tyre size | 270 / 95 R 32 |
| LI / SI / PR | 136 A8 / 136 B |
| TL/TT | TL |
| Brand | Mitas |
| Tread pattern | AC 85 |



Bohnenkamp
■ ■ ● Moving Professionals

Mitas

Notes and features

- The AC 85 is a modern, all-round standard tyre for a wide work spectrum in the field and on the road.
- Its tread pattern provides excellent traction.
- Thanks to its enlarged contact area, the tyre is also suitable for work on grassland.
- The wear-resistant tread compound ensures a long service life.

Technical Informations

| | |
|------------------------------|----------------|
| Item number | 10926481 |
| EAN | 8059971054538 |
| Valid tyre size | 270 / 95 R 32 |
| LI / SI / PR | 136 A8 / 136 B |
| TL/TT | TL |
| Brand | Mitas |
| Tread pattern | AC 85 |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 57,50 |
| Recommended rim size | 9 |
| Permitted rim size | 8, 10 |
| Maximum air pressure [bar]. | 4,00 |
| Section width (mm) | 275 |
| Outer diameter of tyre [mm]. | 1327 |
| Stat. radius (SLR) [mm] | 602 |
| Speed Radius Index (SRI) | 625 |
| Rolling circumference [mm]. | 3976 |
| Tread depth (mm) | 35,0 |
| Number of lugs | 25x2 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 136 A8 | 2240 | 40 | | 4,00 | |
| 136 B | 2240 | 50 | | 4,00 | |