# Bohnenkamp Moving Professionals

05.02.2025

### **TYRES**

Product group	Tyres
Item number	10926494
Valid tyre size	270 / 95 R 48
LI / SI / PR	144 A8 / 141 B
TL/TT	TL
Brand	Mitas
Tread pattern	AC 90



Mitas

#### Notes and features

- The AC 90 is a modern row crop tyre for driving on row crops.
- The rounded lugs and lug shoulders effectively protect crops.
- The tyre is characterised by its excellent traction, high load capacity as well as excellent ride comfort at speeds up to 50 km/h.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

## Bohnenkamp Moving Professionals

### **Technical Informations**

Item number	10926494
EAN	8059971034493
Valid tyre size	270 / 95 R 48
LI / SI / PR	144 A8 / 141 B
TL/TT	TL
Brand	Mitas
Tread pattern	AC 90
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	76,80
Recommended rim size	9
Permitted rim size	W8, W10
Maximum air pressure [bar].	4,00
Section width (mm)	287
Outer diameter of tyre [mm].	1737
Stat. radius (SLR) [mm]	810
Speed Radius Index (SRI)	850
Rolling circumference [mm].	5220
Tread depth (mm)	33,0
Number of lugs	30x2
Lug width (mm)	29
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



### Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
144 A8	2800	40		4,00	
141 B	2575	50		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.