

TYRES

Product group	Tyres
Item number	10927027
Valid tyre size	500 / 85 R 34
LI / SI / PR	178 A8
TL/TT	TL
Brand	Mitas
Tread pattern	SFT



Mitas

Notes and features

- The Mitas SFT was developed for high-performance machines above180 hp.
- Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.



Technical Informations

Item number	10927027
EAN	8059971069433
Valid tyre size	500 / 85 R 34
LI / SI / PR	178 A8
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	168,00
Recommended rim size	16
Permitted rim size	15
Maximum air pressure [bar].	2,80
Section width (mm)	503
Outer diameter of tyre [mm].	1705
Stat. radius (SLR) [mm]	745
Rolling circumference [mm].	5000
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
178 A8	7500	40	Free Rolling	2,80	
166 A8	5300	40	Drive Wheel	2,80	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.