

TYRES

Product group	Tyres
Item number	10927210
Valid tyre size	900 / 60 R 42
LI / SI / PR	183 A8 / 180 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT



Mitas

Notes and features

- The Mitas SFT was developed for high-performance machines above180 hp.
- Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.



Technical Informations

Item number	10927210
item number	
EAN	8059971068924
Valid tyre size	900 / 60 R 42
LI / SI / PR	183 A8 / 180 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	426,80
Recommended rim size	27
Permitted rim size	30
Maximum air pressure [bar].	2,40
Section width (mm)	860
Outer diameter of tyre [mm].	2150
Stat. radius (SLR) [mm]	970
Speed Radius Index (SRI)	1025
Rolling circumference [mm].	6440
Tread depth (mm)	63,0
Number of lugs	20x2
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
183 A8	8750	40		2,40	
180 D	8000	65		2,40	