

TYRES

| | |
|-----------------|----------------|
| Product group | Tyres |
| Item number | 10927210 |
| Valid tyre size | 900 / 60 R 42 |
| LI / SI / PR | 183 A8 / 180 D |
| TL/TT | TL |
| Brand | Mitas |
| Tread pattern | SFT |



Bohnenkamp
■ ■ ● Moving Professionals

Mitas

Notes and features

- The Mitas SFT was developed for high-performance machines above 180 hp.
- Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.

Technical Informations

| | |
|------------------------------|----------------|
| Item number | 10927210 |
| EAN | 8059971068924 |
| Valid tyre size | 900 / 60 R 42 |
| LI / SI / PR | 183 A8 / 180 D |
| TL/TT | TL |
| Brand | Mitas |
| Tread pattern | SFT |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | not necessary |
| Nettogewicht [kg] (gültig) | 426,80 |
| Recommended rim size | 27 |
| Permitted rim size | 30 |
| Maximum air pressure [bar]. | 2,40 |
| Section width (mm) | 860 |
| Outer diameter of tyre [mm]. | 2150 |
| Stat. radius (SLR) [mm] | 970 |
| Speed Radius Index (SRI) | 1025 |
| Rolling circumference [mm]. | 6440 |
| Tread depth (mm) | 63,0 |
| Number of lugs | 20x2 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|--------|--------------------|--------------|---------------|--------------------------|--------------|
| 183 A8 | 8750 | 40 | | 2,40 | |
| 180 D | 8000 | 65 | | 2,40 | |