

TYRES

Product group	Tyres
Item number	10927210
Valid tyre size	900 / 60 R 42
LI / SI / PR	183 A8 / 180 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT



Bohnenkamp
■ ■ ● Moving Professionals

Mitas

Notes and features

- The Mitas SFT was developed for high-performance machines above 180 hp.
- Its big contact area provides excellent traction.
- The flexible sidewalls enable high load capacities even at low inflation pressure.

Technical Informations

Item number	10927210
EAN	8059971068924
Valid tyre size	900 / 60 R 42
LI / SI / PR	183 A8 / 180 D
TL/TT	TL
Brand	Mitas
Tread pattern	SFT
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	426,80
Recommended rim size	27
Permitted rim size	30
Maximum air pressure [bar].	2,40
Section width (mm)	860
Outer diameter of tyre [mm].	2150
Stat. radius (SLR) [mm]	970
Speed Radius Index (SRI)	1025
Rolling circumference [mm].	6440
Tread depth (mm)	63,0
Number of lugs	20x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
183 A8	8750	40		2,40	
180 D	8000	65		2,40	