

TYRES

Product group	Tyres
Item number	10927530
Valid tyre size	280 / 70 R 16
LI / SI / PR	112 A8 / 112 B
TL/TT	TL
Brand	Mitas
Tread pattern	AC 70 T



Mitas

Notes and features

- The AC 70 T is a tractor tyre for heavy field work.
- Its high lugs provide excellent traction.

- Reduced slip thanks to its outstanding self-cleaning properties.
- The tyre is characterised by its versatility and can also be used in vineyards and orchards, for example.



Technical Informations

Item number	10927530
EAN	8059971062373
Valid tyre size	280 / 70 R 16
LI / SI / PR	112 A8 / 112 B
TL/TT	TL
Brand	Mitas
Tread pattern	AC 70 T
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	26,80
Recommended rim size	9
Permitted rim size	8, 10
Maximum air pressure [bar].	2,40
Section width (mm)	285
Outer diameter of tyre [mm].	798
Stat. radius (SLR) [mm]	358
Speed Radius Index (SRI)	390
Rolling circumference [mm].	2390
Tread depth (mm)	30,0
Number of lugs	16x2
Lug width (mm)	37
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
112 A8	1120	40		2,40	
112 B	1120	50		2,40	